

# **Aluminum Foil Tape**

## **Technical Data**

# **Product Description**

Alluminum Tape is made from soft aluminum foil with transparent adhesive for many permanet sealing, holding, splicing or masking applications requiring the protection offered by a foil backing.

- High tensile strength aluminum foil made from special high quality aluminum foil, coated with aggressive solvent-based acrylic adhesive, which provide strong stickiness, good peel strength, high tensile strength and great ageing resistance.
- Base Material: aluminum foil tape. Thickness can be customized.
- Adhesive: acrylic press-sensitive adhesive
- Core: **Φ**75mm
- Widely be used in refrigerators and freezers, etc.

<b>T</b>		$\alpha$	truction
Prod	IIICT (	i nnci	rriiction
1100	ucu		ucuon

Backing: Aluminum Foil

Adhesive: Acrylic Color: Shiny Silver Liner: Tan kraft paper with silicone release

### **Typical Physical Properties**

Total thickness  $0.08 \text{mm} \pm 0.001 \text{mm}$ 

180° peel adhesion 3.47 N/cm

Elongation 32%

Tensile stress 134N/25mm Initial adhesion 2.5cm

Sustained adhesion ≥24hrs, normal temperature

#### **Features**


- Low moisture vapor transmission rate offers excellent sealing and patching performance.
- lacktriangle Best results attained when applied to clean dry surfuace about  $0^{\circ}\mathrm{C}$
- Flame resistant. Class"L" low flammability rating.
- Foil backing provides an excellent reflective surface for both heat and light.
- Good aging performance both indoors and outdoors.

# **Application Ideas**

- Good maskant in electroplating of aluminum because it will not contaminate the bath.
- Seal and patch tears in truck trailers, as well as other outdoor equipment.
- General purpose holding, patching, sealing applications—indoors or out.
- Splicing of thin gauge foils.
- Thermal heat conduction
- Reflect heat away from sentive areas.
- Decorative

Storage	Store under normal conditions of $16^{\circ}\mathrm{C}$ to $27^{\circ}\mathrm{C}$ and $40$ to $60\%$ R.H.in the original carton.	
Shelf Life	To obtain best performance, use this product within 24 months from date of manufacture.	
Specifications	Foil thickness:18, 22, 25, 30. 36. 40µ m Roll width:36, 40, 45, 50, 55, 60mm Roll length:50, 100, 300m	

## **Product Construction**



# **Images**



### DONGGUAN GUANHONG PACKING INDUSTRY CO.,LTD.

FURONGSHA IND.DIST., WANGNIUDUN TOWN, DONGGUAN CITY, G.D.CHINA TEL: 86-769-88518755 FAX: 88518376 E-MAIL: KENNY@DGGUANHONG.COM

http://www.bopppackagingtape.com/